

ran five lks south of corner. I then ran the following broken lines by the duds of J. H. Ellis and R. I. Stephens. Began at center of section ran $N 45^{\circ} W. 52$ poles 10 links to a stone. Thence $N 40^{\circ} W. 31$ poles 16 lks to a stone in the mouth of a branch. During above survey I established corners as given in plat and noted accompanying on opposite page.

M. H. Baskirk Deputy Sur.
I hereby certify the foregoing to be a true copy of notice and record of my work with a true copy of record and notes as furnished by M. H. Baskirk. Witness my hand and seal
A. G. Dillman M. C. Sur.

"Record of Randall Survey"

On Fri. Mar. 30 1888. Mr. Thomas S. Randall and Richard Randall being the only interested parties and having mutually agreed to waive process of notice and agreed to do their own work I began at $S \frac{1}{2}$ m. p. of Sec. 17 T. 8 N. R. 1 W. ran thence $N. 10.84 \frac{1}{2}$ ch. Thence $S 88^{\circ} 20' E$ to 25.60 ch to center of turn-pike perpetuating said point by a letter "W" cut in solid stone 12 in. under ground 34 links $N 88 \frac{1}{2}^{\circ} W.$ with limestone planted over said letter "W". I ran thence $S 88^{\circ} 20' E$ to intersection of common road with turn-pike 11.06 ch. supposed to be at or near the south line of said sec. 17.

Having omitted to qualify above parties before beginning above survey I afterwards, after duly administering the oath took their statement that above work was done impartially ect.

I hereby certify above record to be true
In witness whereof I attach my hand and seal.

A. G. Dillman M. C. S.